SSLC, HSE, DIPLOMA, B.E/B.TECH, M.E/M.TECH, MBA, MCA

Notes Syllabus Question Papers Results and Many more...

Available @

www.AllAbtEngg.com

| _ | | | | | |
|-----------|--|-------|---|------|-----|
| Reg. No.: | | | | | BEL |
| | | _ | _ | | |

Question Paper Code: 91501

B.E./B.Tech. DEGREE EXAMINATIONS, NOVEMBER/DECEMBER 2019 Seventh Semester

Electrical and Electronics Engineering
EE6703 – SPECIAL ELECTRICAL MACHINES
(Regulations 2013)

(Common to: PTEE6703 – Special Electrical Machines for B.E. (Part-Time) Sixth Semester – Electrical and Electronics Engineering – Regulations – 2014)

Time: Three Hours Maximum: 100 Marks

Answer ALL questions

PART - A

(10×2=20 Marks)

- Mention the types of rotors in synchronous reluctance motor.
- Identify the reason for increasing the saliency ratio in synchronous reluctance motor.
- 3. The stepper motor has a step angle of 1.8° and is driven at 4000 pps. Determine (a) Resolution (b) Rotor speed.
- 4. List out any four applications of stepper motor.
- 5. Why is rotor position sensor essential for the operation of switched reluctance motor?
- List out the basic requirements of power semiconductor switching circuits employed for switched reluctance motor.
- 7. Compare conventional DC motor with permanent magnet brushless DC motor.
- A permanent magnet brushless DC motor has a no-load speed of 6000 rpm when connected to 120 V dc supply. Find the armature current when the load torque is 0.5 Nm.
- Distinguish between ideal and practical brushless permanent magnet sine wave motors.
- Draw the permissible operating region in the torque-speed characteristics of permanent magnet synchronous motor.

SSLC, HSE, DIPLOMA, B.E/B.TECH, M.E/M.TECH, MBA, MCA

Notes Syllabus Question Papers Results and Many more...

www.AllAbtEngg.com

Available @

91501

2.

(7)

PART - B

(5×13=65 Marks)

11. a) Explain the constructional features of a synchronous reluctance motor and discuss its working principle.

(OR)

- b) A three phase 230V, 60Hz, 4 pole star connected synchronous reluctance motor with negligible armature resistance has $X_{\rm sd}=22.5~\Omega$ and $X_{\rm sq}=3.5~\Omega$. The load torque is 12.5 Nm. The voltage to frequency ratio is maintained constant at rated value. If the supply frequency is 60Hz, determine (a) torque angle, (b) line current and (c) input power factor.
- a) Describe in detail the construction and working of variable reluctance stepper motor.

(OR)

- b) Draw and explain in detail the static and dynamic characteristics of stepper motor.
- 13. a) i) What is the relationship between torque and current in synchronous reluctance motor? Derive the equation of torque developed in a switched reluctance motor.
 - ii) A switched reluctance motor with six stator poles and four rotor poles has a stator pole arc of 40° and rotor pole arc of 42°. The aligned inductance is 12 mH and the unaligned inductance is 2.8 mH. Saturation can be neglected. Determine the instantaneous torque when the phase current is 7A. Neglect fringing.

(OR)

- b) What is the function of feedback diodes in the power converter circuit of switched reluctance motor? Discuss in detail the working of the power converter circuit that makes use of two transistors and two diodes per phase for a three phase switched reluctance motor with suitable waveform.
- a) Describe with suitable diagram the closed loop control scheme of permanent magnet brushless DC motor.

(OR)

b) Derive the torque equation and torque ratio of permanent magnet brushless DC motor.

SSLC, HSE, DIPLOMA, B.E/B.TECH, M.E/M.TECH, MBA, MCA

Notes Syllabus Question Papers Results and Many more... Available @

www.AllAbtEngg.com

| | | | -3- | | | 91501 |
|------|-----------------------------------|----------------------------|--------------------------------|-----------------------------|--|-------------|
| 15 4 | a) Derive the emf | equation of id | leal and pract | ical permane | nt magnet syn | chronous |
| 10. | motor. | | | | | |
| | | (OR) | | | | 4 |
| | b) i) Draw the ph there from d | erive the toro | que equation. | | | |
| | ii) A 3 phase, 4 | pole perman | ent magnet s | synchronous a | notor has 36 s 20 turns per co magnetic flux | |
| | span is sever calculate the | open circuit | phase emf at | 3000 rpm. | | (7 |
| | | | PART - | | 1.70 | 15=15 Marks |
| 16. | graph repre | of two differe | nt voitage levent and volta | ge. | | (8 |
| | speed of 24 | | nine the comm stepper mot | or having the | aency at each p same step ang | |
| | | (OR) | | | | |
| | | (013) | , hahlar | a DC motor | with perman | ent magnet |
| | b) Compare per synchronous | rmanent mag motor based | gnet brushles on their perf | ss DC motor formance par | with perman ameters. | ent magnet |
| | b) Compare per synchronous | umanent mas | gnet brushles on their perf | ss DC motor formance par | with perman ameters. | ent magnet |
| | b) Compare pe synchronous | umanent mas | gnet brushles on their perf | ss DC motor formance par | with perman ameters. | ent magnet |
| | b) Compare per synchronous | umanent mas | gnet brushles on their perf | ss DC motor formance par | with perman ameters. | ent magnet |
| | b) Compare per synchronous | umanent mas | gnet brushles on their perf | ss DC motor formance par | with perman ameters. | ent magnet |
| | b) Compare per synchronous | umanent mas | gnet brushles on their perf | ss DC motor formance par | with perman ameters. | ent magnet |
| | b) Compare per synchronous | umanent mas | gnet brushles on their perf | ss DC motor formance par | with perman | ent magnet |
| | synchronous | rmanent mag motor based | on their peri | ormance par | amosoro | |
| | synchronous | umanent mas | on their peri | ormance par | with perman | |
| | synchronous | rmanent mag motor based | on their peri | ormance par | amosoro | |
| | synchronous | rmanent mag motor based | on their peri | ormance par | | |
| | synchronous | rmanent mag motor based | on their peri | ormance par | | |
| | synchronous | rmanent mag motor based | on their peri | ormance par | | |