

Reg. No. :

**Question Paper Code : 90338**

B.E./B.Tech. DEGREE EXAMINATIONS, NOVEMBER/DECEMBER 2022.

Seventh Semester

Civil Engineering

CE 8703 — STRUCTURAL DESIGN AND DRAWING

(Regulations 2017)

Time : Three hours

Maximum : 100 marks

Answer ALL questions.

(5 × 20 = 100)

1. (a) A counterfort type retaining wall to suit the following data

Height of wall above ground level = 6m

Safe bearing capacity of the soil site = 160 kN/m<sup>2</sup>

Angle of internal friction = 30°

Density of soil = 16 kN/m<sup>3</sup>

Spacing of counterforts = 3m c/c

Use M20 grade concrete and Fe 415 steel.

- (i) Design the retaining wall (12)  
(ii) Draw the sectional elevation of vertical wall and base slab. (8)

Or

- (b) A RCC cantilever type retaining wall is required to support the earth to a height of 5m above the ground level. The top surface of the backfill is horizontal. The safe bearing capacity of the soil is 180 kN/m<sup>2</sup>. Unit weight of soil is 17 kN/m<sup>3</sup>. The angle of repose of soil is 30°. The coefficient of friction between concrete and soil is 0.55. Use M20 grade concrete and Fe415 grade steel.

- (i) Design the retaining wall (12)  
(ii) Draw the sectional elevation of vertical wall and base slab. (8)

2. (a) The interior panel of a flat slab  $5.6 \times 6.6$  m in size, for a super – imposed load of  $7 \text{ kN/m}^2$ . Provide two way reinforcement. Use M20 concrete and Fe 415 steel.
- (i) Design the Flat slab. (12)
- (ii) Sketch the reinforcement details. (8)

Or

- (b) A solid slab bridge for class A loading for the following data  
Clear span = 4.5m,  
Clear width of the road way = 7m,  
average thickness of wearing coat = 80mm,  
Use M20 grade,
- (i) Design the solid slab bridge. (15)
- (ii) Sketch the reinforcement details. (5)

3. (a) A ground level circular water tank has capacity of 5,00,000 litres. The bottom of the tank is fixed and the top is free. The safe bearing capacity of the soil is  $250 \text{ kN/m}^2$ . Use M30 grade concrete and Fe415 grade steel
- (i) Design the water tank (15)
- (ii) Draw the sectional elevation of vertical wall and plan of base slab. (5)

Or

- (b) An underground rectangular tank  $10 \text{ m} \times 6 \text{ m} \times 3 \text{ m}$  deep.  
The tank is cover at top. Take density of soil as  $16 \text{ kN/m}^2$  and angle of repose as  $30^\circ$ .
- (i) Design the underground water tank (15)
- (ii) Draw the sectional elevation of vertical wall and plan of base slab. (5)

4. (a) A steel roof truss to the following data :
- Span of the truss = 10 m  
Type of truss = Fan type  
Roof cover = Galvanized corrugated sheeting  
Spacing of roof trusses = 4.5 m  
Wind pressure =  $1 \text{ kN/m}^2$
- (i) Design a steel roof truss (15)
- (ii) Draw the elevation of the roof truss and details of any one joint. (5)

Or



- (b) A channel section purlin for the following data :

Spacing of trusses = 4.2 m

Spacing of purlin = 2 m

Live load on galvanized iron roofing sheets =  $0.6 \text{ kN/m}^2$

Wind load =  $1.4 \text{ kN/m}^2$

Slope of main rafter =  $31^\circ$ .

(i) Design a channel section for purlin. (12)

(ii) Draw structural details. (8)

5. (a) A welded plate girder of 30 m span to support a live load of  $75 \text{ kN/m}$  uniformly distributed over the span.

(i) Design a welded plate girder. (12)

(ii) Draw the longitudinal elevation, cross section and plan of the plate girder. (8)

Or

- (b) Design a gantry girder for an industrial building carrying a manually operated overhead travelling crane for the following data

(i) Crane capacity = 200 kN

(ii) Self weight of the crane girder excluding trolley = 200 kN

(iii) Self weight of the trolley, electric motor, hook, etc = 50 kN

(iv) Minimum approach of the crane hook to the gantry girder = 1.20 m

(v) Wheel base = 3.60 m

(vi) c/c distance between gantry rails = 20 m

(vii) c/c between columns = 8 m

(viii) Self weight of rail section = 300 N/m

(ix) Diameter of crane wheels = 150 mm

(x) Grade of steel = Fe 410

(1) Design the gantry girder (12)

(2) Draw the structural details. (8)